Activated Carbon Data Sheet

AquaPur 800GA-US 8x30

Tetrasolv FILTRATION

Applications

Potable Water Filtration

POU/POE Filters

Chemical Refining

Wastewater Treatment

Features/Benefits

Virgin Carbon

Low Ash

High Activity

High Hardness

Low Dust

Packaging

500 kg bulk bags

25 kg bags

Tetrasolv
444 E. 29th Street
Anderson, in 46016

14549 Minetta Street
Houston, TX 77035

Phone: 765-643-3941
E-mail: info@tetrasolv.com

AquaPur 800GA-US 8x30 is a virgin activated carbon produced in the USA from selected low ash bituminous coal. This granular carbon has excellent adsorptive properties for removing organics for potable water treatment or impurities from industrial or remediation applications.

AquaPur 800GA-US 8x30 is available in various packaging and can be a component of a supplied turnkey

Specifications

Iodine Number	900 mg/g min
Moisture	5% max as packed
Mesh Size +8 mesh	less than 5%
Mesh Size –30 mesh	less than 5%

Typical Properties

Ball Pan Hardness	90
Abrasion Number	75
Apparent Density	31-33 lbs/ft3
Ash	8% max



CAUTION *Activated carbon can remove oxygen from air under wet or humid conditions. Care should be taken when entering confined spaces where wet activated carbon is present. Use proper breathing apparatus to prevent prolong dust exposure.*

NOTICE *Tetrasolv reserves the right to change product specifications without prior notification. The information contained in this datasheet is intended to assist a customer in the evaluation and carbon selection. Tetrasolv or any of its affiliations assumes no obligation or liability for the usage of the information in this datasheet. No guarantees or warranties, expressed or implied, are provided and the user must accept full responsibility for performance of carbon based on this data.*

Revised Jan 2023